

# SAFETY DATA SHEET

Page 1 of 4

# **SECTION 1. IDENTIFICATION**

Product Name: 949 BRT WHITE HS WB STRIPPABLE Product Code: 949 Manufacturer's Name: Carbit Paint Company Address: 927 W. Blackhawk St, Chicago, IL 60642 Information Phone: 312-280-2300 Emergency Phone: INFOTRAC 800-535-5053 Date Prepared: 10/14/2015

# SECTION 2. HAZARDS IDENTIFICATION

#### GHS Ratings:

**GHS Hazards:** 

### GHS Precautions:

### Signal Word:

There are no GHS ratings that apply to this product at this time.

# SECTION 3. COMPOSITION

Chemical Name	CAS number	Weight Concentration %
Limestone	1317-65-3	10.00% - 20.00%
Titanium dioxide	13463-67-7	5.00% - 10.00%
Poly(oxy-1,2-ethanediyl), .alpha(4-nonylphenyl) omegahydroxy-, branched	127087-87-0	1.00% - 5.00%
Distillates, petroleum, hydrotreated heavy paraffinic	64742-54-7	1.00% - 5.00%

## **SECTION 4. FIRST-AID MEASURES**

**Inhalation:** Move individual to fresh air. If breathing is difficult, administer oxygen and seek medical attention.

**Eye Contact:** If irritation occurs, move away from exposed area and flush eyes with water for 15 minutes. If irritation continues, seek medical attention.

Skin Contact: . Remove contaminated clothing. Flush exposed area with water and wash with soap and water. If irritation occurs, seek medical attention.

Ingestion: Do not induce vomiting. If vomiting does occur, seek medical attention and contact poison control.

## SECTION 5. FIRE-FIGHTING MEASURES

Flash Point: 108 C (226 F)

LEL: No Data

UEL: No Data

**Special Firefighting Procedures:** Normal fire fighting procedures may be used. Water may be used to cool containers to prevent pressure build up.

Extinguishing Media: Foam, CO2, Dry Chemical

**Unusual Fire and Explosion Hazards:** Material will not ignite or support combustion unless water has evaporated. Dried solids may burn.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

In Case of Spill or Leak: If spilled, dike areas with sand and absorb with an absorbent material.

**Special Precautions:** Protect from freezing, keep containers closed and stored in a covered area. Do not smoke or eat in work area. Keep away from children.

## SECTION 7. HANDLING AND STORAGE

Handling and Storing Precautions: Keep container closed and from freezing when not in use. Store in original container away from incompatible materials.

Hygienic Practices: As with all chemicals take all necessary precautions to avoid prolonged contact.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Limestone 1317-65-3	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	Not Established	NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
Titanium dioxide 13463-67-7	15 mg/m3 TWA (total dust)	10 mg/m3 TWA	Not Established
Poly(oxy-1,2-ethanediyl) , .alpha(4-nonylphenyl) omegahydroxy-, branched 127087-87-0	Not Established	Not Established	Not Established
Distillates, petroleum, hydrotreated heavy paraffinic 64742-54-7	Not Established	Not Established	Not Established

**Engineering Controls:** Facilities that are storing or using these materials should have proper ventilation equipment, and proper eyewash and safety shower facilities.

Ventilation: Provide sufficient mechanical ventilation to maintain concentrations below exposure limits.

**Respiratory Protection:** If engineering controls do not maintain airborne concentrations below recommended exposure limits, a suitable respirator must be worn. Avoid prolonged or repeated breathing of vapors.

Hand Protection: Wear chemical resistant gloves, neoprene, plastic coated, etc.

**Eye Protection:** Chemical splash proof safety goggles in compliance with OSHA regulations. If splashing is possible, wear necessary protective clothing and boots. Follow hand and eye safety procedures.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance: No Data Vapor Pressure: No Data Vapor Density: No Data Specific Gravity: 1.180757784 Freezing point: No Data Boiling range: 100°C Evaporation rate: No Data Explosive Limits: 0% Autoignition temperature: 371°C Viscosity: No Data VOC (Incl H2O & Exempt) Ib/gal 0.17

Odor: No Data Odor threshold: No Data pH: No Data Melting point: No Data Solubility: No Data Flash point: 226 F,108 C Flammability: No Data Partition coefficient (n- No Data octanol/water): Decomposition temperature: No Data VOC (Excl H2O & Exempt) Ib/gal 0.44

# SECTION 10. REACTIVITY AND STABILITY

Stability: UNSTABLE

Incompatibilities: Avoid strong oxidizing agents, strong acids and bases.

#### Hazardous Decomposition: No Data Available

### SECTION 11. TOXICOLOGICAL INFORMATION

**Emergency Overview:** Harmful if inhaled or ingested. May cause eye and skin irritation. If exposed for long periods, may cause dizziness, headache or nausea.

Conditions Aggravated: Pre-existing eye, skin, heart and blood disorders may be aggravated by exposure to product.

#### Mixture Toxicity (Calculation Method):

Routes of Entry: Ingestion, inhalation, skin absorption, skin contact, eye absorption, and eye contact.

Target Organs: Damage may be caused to blood, central nervous system, eyes, heart, kidneys, liver, skin, and upper respiratory tract.

Carcinogenicity

None		N/A	
	LOGICAL INFORMATION		

Ecological Information: Ecological data are not available.

## SECTION 13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods: Dispose of in accordance with local, state and federal regulations. Do not incinerate closed container.

## SECTION 14. TRANSPORT INFORMATION

Agency	Proper Shipping Name
DOT	NOT REGULATED

UN Number

Packing Group

Hazard Class

### SECTION 15. REGULATORY INFORMATION

### California Proposition 65 Carcinogens: Titanium dioxide 13463-67-7

Quartz 14808-60-7

### SARA 313 Chemicals:

- None

# **SECTION 16. OTHER INFORMATION**

The information herein is furnished without warranty of any kind. Users should consider this data only as a supplement to the other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees.